"STANDARD K.D." SINGLE TIER LOCKER (18" OR 24" WIDE) (PRODUCT No. SK -1) LOCKER DETAILS: ELEVATION ' DOOR & FRAME COLOR = BODY COMPONENT COLOR =729 PARCHMENT TNP = HANDLE = LIFT (S.S. RECESSED DRAWN) DOOR VENTILATION = 3' LOUVERS SIDE VENTILATION = SOLID BASE = LOCKS = 10" HINGE = CONTINUOUS PIANO HINGE CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL. GAUGES 16 GA., C.R.S. DOOR = (9" WIDE DOOR = 18 GA., C.R.S.) FRAME = 16 GA., C.R.S 24 GA., C.R.S. TNP = BOTTOM = 24 GA., C.R.S. SHELVES = 24 GA., C.R.S. SIDES = 24 GA., C.R.S. BACKS = 24 GA., C.R.S. LATCHING: (WARDROBE) THREE POINT RECESSED ON LOCKER DOORS 48" AND OVER, TWO POINT RECESSED ON ON LOCKER DOORS 36' TO 20'. AUTOMATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP. FRONT VIEW SIDE VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL Checked By: Drawn By: Customer: CUSTOMER PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DRAFTER NONE DATE | Hallowell^{*} DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION, ONLY LIST INDUSTRIES Customer Order Number: PO# RESERVES THE RIGHT TO ALTER ANY DESIGN, ANY UNAUTHORIZED Acad Number: PAGE NUMBER Sheet # Of # Revision: MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES. Description: JOB NAME Drawing Number:

JOB LOCATION

TOLERANCES UNLESS SPECIFIED

DECIMALS: ±.010

DEGREES: ±1°

FRACTIONS: ±1/32

FOLDER NUMBER